Multi-Meter Assemblies - 208Y/120 Vac 3 phase 4 wire in, 1 phase 3 wire out									
	Amperes		Main Bus						
	Per	Number of	Rating in						
Manufacture	Position	Positions	Amperes	Catalog Number	Description				
		2	800	EZML312225	Ringless design device, must be supplied with 5 -				
Square D	225	3	800	EZML313225	jaw lever bypass meter socket type HQ-5 and				
		4	800	EZML314225	individual position barrel lock covers.				

	Multi-Mete	r Assemblies	- 208Y/120	Vac 3 phase 4 wire	or 240/120 Delta in, 3 phase 4 wire out
	Amperes		Main Bus	·	·
	Per	Number of	Rating in		
Manufacture	Position	Positions	Amperes	Catalog Number	Description
Square D	225	1	1200	EZML331225	Ringless design device, must be supplied with 7 - jaw lever bypass meter socket type HQ-7 and individual position barrel lock covers.
		2	1200	EZML332225	
		3	1200	EZML333225	
		4	1200	EZML334225	
	100	1	1200	WML13100RJ	Ringless design device, must be supplied with 7 - jaw lever bypass meter socket type HQ-7 and individual position barrel lock covers.
Siemens		2	1200	WML23100RJ	
Siemens		3	1200	WML33100RJ	
		4	1200	WML43100RJ	
	225	1	1200	WCL2442B3T1RJ	Ringless design device, must be supplied with 7 - jaw lever bypass meter socket type HQ-7 and individual position barrel lock covers. For use as a house meter, contains breakers.
		1	1200	WCL2442B3T2RJ	
		1	1200	WCL2442B3T3RJ	
Siemens		1	1200	WCL2442B3T4RJ	
		1	1200	WCL2442B3T5RJ	
		1	1200	WCL2442B3T6RJ	
		1	1200	WCL2442B3T7RJ	
		1	1200	WCL2442B3T8RJ	
		1	1200	WCL2442B3T9RJ	
		1	1200	WML13225RJ	Ringless design device, must be supplied with 7 - jaw lever bypass meter socket type HQ-7 and individual position barrel lock covers.
		2	1200	WML23225RJ	
		3	1200	WML33225RJ	
		4	1200	WML43225RJ	
Eaton / Cutler - Hammer	225	1	1200	37MM120R12	Ringless design device, must be supplied with 7 - jaw meter socket and lever bypass. Must be supplied with individual position barrel lock covers.
		2	1200	37MM220R12	
		3	1200	37MM320R12	
		4	1200	37MM420R12	
GE Power	225	1	1200	TMPR312122R	Ringless design device, must be supplied with 7 - jaw meter socket and lever bypass. Must be supplied with individual position barrel lock covers.
		2	1200	TMPR312222R	
		3	1200	TMPR312322R	
		4	1200	TMPR312422R	