

| Multi-Meter Assemblies - 208Y/120 Vac 3 phase 4 wire in, 1 phase 3 wire out | | | | | |
|---|----------------------|---------------------|----------------------------|----------------|--|
| Manufacture | Amperes Per Position | Number of Positions | Main Bus Rating in Amperes | Catalog Number | Description |
| Square D | 225 | 2 | 800 | EZML312225 | Ringless design device, must be supplied with 5 - jaw lever bypass meter socket type HQ-5 and individual position barrel lock covers. |
| | | 3 | 800 | EZML313225 | |
| | | 4 | 800 | EZML314225 | |
| Siemens | 200 | 1 | 1200 | W2MM1200 | Ringless design device, must be supplied with 5 - jaw meter socket and lever bypass. Must be supplied with individual position barrel lock covers. |
| | | 2 | 1200 | W2MM2AB200 | |
| | | 2 | 1200 | W2MM2BC200 | |
| | | 2 | 1200 | W2MM2CA200 | |
| | | 3 | 1200 | W2MM3200 | |
| | | 4 | 1200 | W2MM4AB200 | |
| | | 4 | 1200 | W2MM4BC200 | |
| 4 | 1200 | W2MM4CA200 | | | |

| Multi-Meter Assemblies - 208Y/120 Vac 3 phase 4 wire or 240/120 Delta in, 3 phase 4 wire out | | | | | |
|--|----------------------|---------------------|----------------------------|----------------|--|
| Manufacture | Amperes Per Position | Number of Positions | Main Bus Rating in Amperes | Catalog Number | Description |
| Square D | 225 | 1 | 1200 | EZML331225 | Ringless design device, must be supplied with 7 - jaw lever bypass meter socket type HQ-7 and individual position barrel lock covers. |
| | | 2 | 1200 | EZML332225 | |
| | | 3 | 1200 | EZML333225 | |
| | | 4 | 1200 | EZML334225 | |
| Siemens | 100 | 1 | 1200 | WML13100RJ | Ringless design device, must be supplied with 7 - jaw lever bypass meter socket type HQ-7 and individual position barrel lock covers. |
| | | 2 | 1200 | WML23100RJ | |
| | | 3 | 1200 | WML33100RJ | |
| | | 4 | 1200 | WML43100RJ | |
| Siemens | 225 | 1 | 1200 | WML13225RJ | Ringless design device, must be supplied with 7 - jaw lever bypass meter socket type HQ-7 and individual position barrel lock covers. |
| | | 2 | 1200 | WML23225RJ | |
| | | 3 | 1200 | WML33225RJ | |
| | | 4 | 1200 | WML43225RJ | |
| Eaton / Cutler - Hammer | 225 | 1 | 1200 | 37MM120R12 | Ringless design device, must be supplied with 7 - jaw meter socket and lever bypass. Must be supplied with individual position barrel lock covers. |
| | | 2 | 1200 | 37MM220R12 | |
| | | 3 | 1200 | 37MM320R12 | |
| | | 4 | 1200 | 37MM420R12 | |